

(BA) 直管

SUS-316 TP-S-BA

単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)	
1.58	X 0.4	X 2,000		
2	X 0.5	X 2,000		
3	X 0.5	X 2,000		
	1.0	X 2,000		
3.18	X 0.5	X 2,000		
	0.72	X 2,000		
		X 4,000		
	1.0	X 2,000		
4	X 0.5	X 2,000		
	1.0	X 2,000		
4.76	X 0.8	X 2,000		
5	X 1.0	X 2,000		
6	X 1.0	X 2,000		
		X 4,000		
	1.2	X 4,000		
	1.5	X 4,000		
6.35	X 0.89	X 2,000		
		X 4,000		
	1.0	X 2,000		
		X 4,000		
	1.24	X 4,000		
	1.65	X 4,000		
8	X 1.0	X 2,000		
		X 4,000		
	1.5	X 4,000		
9.53	X 0.89	X 2,000		
		X 4,000		
	1.0	X 2,000		
		X 4,000		
	1.24	X 4,000		
	1.65	X 4,000		
10	X 1.0	X 2,000		
		X 4,000		
	1.5	X 4,000		
12	X 1.0	X 4,000		
	1.2	X 4,000		
	1.5	X 4,000		
12.7	X 1.0	X 2,000		
		X 4,000		
	1.24	X 2,000		

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)	
12.7	X 1.24	X 4,000		
	1.65	X 4,000		
	2.11	X 4,000		
15.88	X 1.0	X 4,000		
	1.24	X 4,000		
	1.65	X 4,000		
19.05	X 1.24	X 4,000		
	1.65	X 4,000		

SUS-316L TP-S-BA

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)	
3.18	X 0.72	X 2,000		
6	X 1.0	X 4,000		
6.35	X 0.89	X 2,000		
		X 4,000		
	1.0	X 2,000		
		X 4,000		
8	X 1.0	X 4,000		
9.53	X 1.0	X 2,000		
		X 4,000		
	1.24	X 4,000		
10	X 1.0	X 4,000		
12	X 1.0	X 4,000		
12.7	X 1.0	X 2,000		
		X 4,000		
	1.24	X 2,000		
		X 4,000		
15.9	X 1.0	X 4,000		
19.1	X 1.24	X 4,000		
	1.65	X 4,000		
21.7	X 1.65	X 4,000		
25.4	X 1.65	X 4,000		
27.2	X 1.65	X 4,000		
34	X 1.65	X 4,000		
48.6	X 1.65	X 4,000		
60.5	X 1.65	X 4,000		
48.6	X 1.65	X 4,000		
60.5	X 1.65	X 4,000		