

# BA-コイル品

## SUS-304 TP-S-BA

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)	
3	× 0.5	× 30M		
		× 50M		
	1.0	× 30M		
		× 50M		
3.18	× 0.5	× 30M		
		× 50M		
	0.72	× 30M		
4	× 0.5	× 30M		
		× 50M		
6	× 1.0	× 30M		
		× 50M		
		× 100M		
6.35	× 1.0	× 30M		
		× 50M		
8	× 1.0	× 30M		
		× 50M		
9.53	× 1.0	× 30M		
		× 50M		
10	× 1.0	× 30M		
		× 50M		
12	× 1.0	× 30M		
		× 50M		
12.7	× 1.0	× 30M		
		× 50M		
		× 50M		

## SUS-316 TP-S-BA 単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)	
3	× 0.5	× 30M		
3.18	× 0.5	× 30M		
		0.72	× 30M	
6	× 1.0	× 30M		
		× 50M		
		× 100M		
6.35	× 1.0	× 30M		
		× 50M		
8	× 1.0	× 30M		
		× 50M		
9.53	× 1.0	× 35M		
		× 57M		
10	× 1.0	× 30M		
		× 50M		
12	× 1.0	× 30M		
		× 30M		

## SUS-316L TP-S-BA

6	× 1.0	× 30M		
		× 50M		
		× 100M		
6.35	× 1.0	× 30M		
8	× 1.0	× 30M		
		× 50M		
9.53	× 1.0	× 30M		
10	× 1.0	× 30M		
		× 50M		