

新サイズ SUS 304 機械構造用シームレス鋼管

外 径 (O.D) mm	内 径 (I.D) mm	厚 さ (W.T) mm	長 さ (L) m
85.0	30.0	27.5	2.0 - 3.5
90.0	35.0	27.5	3.5 - 5.0
95.0	35.0	30.0	3.5 - 5.0
100.0	50.0	25.0	3.5 - 5.0
100.0	40.0	30.0	3.5 - 5.0
110.0	50.0	30.0	3.5 - 5.0
110.0	40.0	35.0	3.5 - 5.0
120.0	60.0	30.0	3.5 - 5.0
120.0	40.0	40.0	3.5 - 5.0
130.0	70.0	30.0	3.5 - 5.0
130.0	50.0	40.0	3.5 - 5.0
140.0	60.0	40.0	2.5 - 4.0
160.0	60.0	50.0	3.0 - 4.0
160.0	80.0	40.0	2.5 - 4.0
180.0	100.0	40.0	3.5 - 5.0
180.0	80.0	50.0	2.5 - 4.0
180.0	60.0	60.0	2.5 - 3.5
190.0	110.0	40.0	2.5 - 3.5
190.0	90.0	50.0	2.5 - 3.5
190.0	70.0	60.0	2.0 - 3.5
200.0	120.0	40.0	2.5 - 3.5
200.0	100.0	50.0	1.5 - 2.5
200.0	80.0	60.0	1.5 - 2.5
250.0	170.0	40.0	1.5 - 2.5
250.0	150.0	50.0	1.5 - 2.5

※許容差

外径 -0+2%

内径 +0-2%