

溶 接 管

SUS-304 TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
6	× 0.5	× 4,000	
	1.0	× 4,000	
6.35	× 1.0	× 4,000	
7	× 1.0	× 4,000	
8	× 0.5	× 4,000	
	1.0	× 4,000	
	1.5	× 4,000	
9	× 1.0	× 4,000	
9.53	× 1.0	× 4,000	
10	× 0.5	× 4,000	
	1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
10.5	× 1.0	× 4,000	
	1.2	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
12	× 0.5	× 4,000	
	1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
12.7	× 1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
13	× 1.0	× 4,000	
13.8	× 1.2	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
	2.2	× 4,000	
	3.0	× 4,000	
14	× 1.0	× 4,000	
15	× 1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
16	× 1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
17.3	× 1.2	× 4,000	
	1.5	× 4,000	

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
17.3	× 2.0	× 4,000	
	2.5	× 4,000	
	3.0	× 4,000	
18	× 1.0	× 4,000	
19	× 1.0	× 4,000	
	1.2	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
20	× 1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
21.7	× 1.2	× 4,000	
	1.5	× 4,000	
	2.0	× 2,000	
		× 3,000	
		× 4,000	
		× 6,000	
	2.5	× 2,000	
		× 3,000	
		× 4,000	
		× 6,000	
22	× 1.0	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
25.4	× 1.2	× 4,000	
	1.5	× 4,000	
	2.0	× 4,000	
27.2	× 1.2	× 4,000	
	1.5	× 4,000	
	2.0	× 2,000	
		× 3,000	
		× 4,000	
		× 6,000	

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-304 TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
27.2	× 2.5	× 2,000	
		× 3,000	
		× 4,000	
	3.0	× 6,000	
		× 2,000	
		× 4,000	
		× 5,000	
30	× 1.5	× 4,000	
		× 4,000	
		× 4,000	
32	× 1.2	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
34	× 1.2	× 4,000	
		× 4,000	
		× 2,000	
		× 3,000	
		× 4,000	
		× 6,000	
	2.5	× 4,000	
		× 2,000	
		× 2,500	
		× 3,000	
	3.0	× 4,000	
		× 5,000	
		× 6,000	
3.5	× 4,000		
	× 6,000		
	× 6,000		
4.0	× 4,000		
	× 6,000		
	× 6,000		
38	× 1.5	× 4,000	
		× 4,000	
		× 4,000	
40	× 2.0	× 4,000	
42.7	× 1.2	× 4,000	
		× 4,000	
		× 4,000	

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
42.7	× 2.0	× 6,000	
		× 2,000	
		× 4,000	
	3.0	× 6,000	
		× 4,000	
		× 6,000	
	3.5	× 4,000	
× 6,000			
× 6,000			
4.0	× 4,000		
	× 4,000		
	× 6,000		
45	× 2.0	× 4,000	
48.6	× 1.2	× 4,000	
		× 4,000	
		× 4,000	
	2.0	× 6,000	
		× 2,000	
		× 2,500	
		× 3,000	
	3.0	× 4,000	
		× 4,000	
		× 5,000	
		× 6,000	
3.5	× 4,000		
	× 6,000		
	× 6,000		
4.0	× 4,000		
	× 6,000		
	× 6,000		
5.1	× 4,000		
	× 6,000		
	× 6,000		
50.8	× 1.5	× 4,000	
		× 4,000	
		× 4,000	
60.5	× 1.5	× 4,000	
		× 4,000	
		× 6,000	
	3.0	× 2,000	
		× 2,500	
		× 3,000	
3.5	× 4,000		
	× 4,000		
	× 6,000		

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-304 TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)	
60.5	× 4.0	× 4,000		
		× 6,000		
	5.0	× 4,000		
		5.5		× 4,000
		× 6,000		
63.5	× 2.0	× 4,000		
76.3	× 2.0	× 4,000		
		× 6,000		
		3.0		× 2,000
				× 2,500
				× 3,000
				× 4,000
				× 5,000
				× 6,000
	3.5	× 4,000		
		× 6,000		
	4.0	× 4,000		
		× 6,000		
	5.0	× 4,000		
	× 6,000			
7.0	× 4,000			
	× 6,000			
89.1	× 2.0	× 4,000		
		× 6,000		
		3.0		× 2,000
		× 3,000		
		× 4,000		
		× 5,000		
		× 6,000		
	4.0	× 2,000		
		× 3,000		
		× 4,000		
		× 6,000		
5.0	× 4,000			
5.5	× 4,000			
	× 6,000			
7.6	× 4,000			
	× 6,000			
101.6	× 2.0	× 4,000		

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
101.6	× 2.0	× 6,000	
		3.0	
		× 6,000	
	4.0	× 4,000	
		× 6,000	
		5.7	
		× 6,000	
114.3	× 2.0	× 4,000	
		× 6,000	
	3.0	× 2,000	
		× 2,500	
		× 3,000	
		× 4,000	
		× 5,000	
		× 6,000	
	4.0	× 2,000	
		× 3,000	
		× 4,000	
		× 6,000	
	5.0	× 4,000	
	6.0	× 4,000	
		× 6,000	
	8.6	× 4,000	
		× 6,000	
139.8	× 2.0	× 4,000	
		3.0	
		× 6,000	
	3.5	× 4,000	
		× 6,000	
	4.0	× 4,000	
		× 6,000	
	5.0	× 4,000	
		× 6,000	
	6.6	× 4,000	
		× 6,000	
9.5	× 4,000		
	× 6,000		

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-304 TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)	外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)	
165.2	× 3.0	× 4,000		*	267.4	× 6,000		
		× 4,000				× 15.1		× 6,000
	× 6,000	× 3.0				× 4,000		
	× 4,000					× 6,000		
	× 6,000	4.0				× 4,000		
	× 4,000	4.5				× 6,000		
	× 6,000	4.5				× 4,000		
	× 4,000	6.5				× 6,000		
× 6,000	6.5	× 4,000						
190.7	× 3.0	× 4,000		*	355.6	× 4,000		
		× 4,000				× 4.0		× 6,000
		× 4,000				5.0		× 4,000
216.3	× 3.0	× 4,000		*	406.4	× 6,000		
		× 6,000				8.0		× 4,000
	× 4,000	8.0				× 6,000		
	× 6,000	11.1				× 4,000		
	× 4,000	11.1				× 6,000		
	× 6,000	19				× 4,000		
	× 4,000	19				× 6,000		
	× 6,000	4.0				× 4,000		
267.4	× 3.0	× 4,000		*	457.2	× 6,000		
		× 4,000				× 4.0		× 6,000
	× 6,000	5.0				× 4,000		
	× 4,000	5.0				× 6,000		
	× 6,000	6.0				× 4,000		
	× 4,000	6.0				× 6,000		
	× 6,000	12.7				× 4,000		
	× 4,000	12.7				× 6,000		
267.4	× 3.0	× 4,000		*	457.2	× 6,000		
		× 6,000				× 4.0		× 6,000
	× 4,000	5.0				× 4,000		
	× 6,000	5.0				× 6,000		
	× 4,000	6.0				× 4,000		
	× 6,000	6.0				× 6,000		
	× 4,000	9.3				× 4,000		
× 6,000	9.3	× 6,000						
267.4	× 3.0	× 4,000		*	457.2	× 6,000		
		× 6,000				× 4.0		× 6,000
		× 4,000				5.0		× 4,000
267.4	× 3.0	× 4,000		*	457.2	× 6,000		
		× 6,000				6.0		× 4,000
	× 4,000	6.0				× 6,000		
	× 6,000	15.1				× 4,000		

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-304 TP-A

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
* 457.2	× 8.0	× 4,000	
		× 6,000	
		14.3 × 4,000 × 6,000	
* 508	× 4.0	× 4,000	
		× 6,000	
		5.0 × 4,000	
		× 6,000	
		6.0 × 4,000	
		× 6,000	
* 558.8	× 5.0	× 4,000	
		5.5 × 4,000	
		× 6,000	
		6.0 × 4,000	
* 609.6	× 6.0	× 4,000	
		× 6,000	
		6.5 × 4,000	
* 660.4	× 5.5	× 4,000	
		× 4,000	
		8.0 × 4,000	
* 711.2	× 6.0	× 4,000	
		8.0 × 4,000	

SUS-304L TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
17.3	× 2.0	× 4,000	
		3.0 × 4,000	
21.7	× 2.0	× 4,000	
		2.5 × 4,000	
		3.0 × 4,000	
27.2	× 2.0	× 4,000	
		2.5 × 4,000	
		3.0 × 4,000	
34	× 3.0	× 4,000	
		3.5 × 4,000	
42.7	× 3.0	× 4,000	
		48.6 × 3.0 × 4,000	
48.6	× 3.0	× 4,000	
		4.0 × 4,000	
60.5	× 3.0	× 4,000	
		3.5 × 4,000	
76.3	× 3.0	× 4,000	
		3.5 × 4,000	
		5.0 × 4,000	
89.1	× 3.0	× 4,000	
		4.0 × 4,000	
		5.5 × 4,000	
114.3	× 3.0	× 4,000	
		4.0 × 4,000	
		6.0 × 4,000	
139.8	× 3.5	× 4,000	
		5.0 × 4,000	
		6.6 × 4,000	
165.2	× 3.5	× 4,000	
		5.0 × 4,000	
		7.1 × 4,000	
216.3	× 4.0	× 4,000	
		6.5 × 4,000	

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-316 TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
13.8	× 1.5	× 4,000	
		× 4,000	
17.3	× 1.5	× 4,000	
		× 4,000	
		× 4,000	
21.7	× 2.0	× 4,000	
		× 4,000	
		× 4,000	
27.2	× 2.0	× 4,000	
		× 4,000	
		× 4,000	
34	× 2.0	× 4,000	
		× 4,000	
		× 6,000	
		× 4,000	
42.7	× 2.0	× 4,000	
		× 4,000	
		× 6,000	
		× 4,000	
48.6	× 2.0	× 4,000	
		× 4,000	
		× 6,000	
		× 4,000	
		× 4,000	
60.5	× 2.0	× 4,000	
		× 4,000	
		× 6,000	
		× 4,000	
		× 4,000	
76.3	× 2.0	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
89.1	× 2.0	× 4,000	

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
89.1	× 3.0	× 4,000	
		× 6,000	
		× 4,000	
		× 6,000	
101.6	× 3.0	× 4,000	
		× 4,000	
		× 4,000	
114.3	× 2.0	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
139.8	× 3.0	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
165.2	× 3.0	× 4,000	
		× 6,000	
		× 4,000	
		× 6,000	
		× 4,000	
216.3	× 3.0	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
267.4	× 3.0	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
318.5	× 3.0	× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	
		× 4,000	

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-316L TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
13.8	× 2.0	× 4,000	
17.3	× 2.0 3.0	× 4,000 × 4,000	
21.7	× 2.0 2.5 3.0	× 4,000 × 6,000 × 4,000 × 4,000 × 6,000	
27.2	× 2.0 2.5 3.0	× 4,000 × 4,000 × 4,000	
34	× 2.0 3.0 3.5 4.0	× 4,000 × 4,000 × 6,000 × 4,000 × 4,000	
42.7	× 2.0 3.0 3.5 4.0	× 4,000 × 4,000 × 4,000 × 4,000	
48.6	× 1.5 2.0 3.0 4.0 5.1	× 4,000 × 4,000 × 4,000 × 6,000 × 4,000 × 6,000 × 4,000	
60.5	× 2.0 3.0 3.5 4.0 5.5	× 4,000 × 4,000 × 6,000 × 4,000 × 4,000 × 4,000	
76.3	× 2.0 3.0 3.5 4.0 5.0	× 4,000 × 4,000 × 6,000 × 4,000 × 4,000 × 4,000	

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
76.3	× 7.0	× 4,000 × 6,000	
89.1	× 2.0 3.0 4.0 5.5 7.6	× 4,000 × 4,000 × 6,000 × 4,000 × 6,000 × 4,000 × 6,000 × 4,000	
114.3	× 3.0 4.0 6.0	× 4,000 × 4,000 × 4,000	
139.8	× 3.0 3.5 4.0 5.0 6.6	× 4,000 × 4,000 × 4,000 × 4,000 × 4,000	
165.2	× 3.0 3.5 5.0 7.1 11.1	× 4,000 × 4,000 × 4,000 × 4,000 × 4,000	
216.3	× 3.0 4.0 6.5 8.2	× 4,000 × 4,000 × 4,000 × 6,000 × 4,000 × 6,000	
267.4	× 3.0 4.0 6.5 9.3	× 4,000 × 4,000 × 4,000 × 6,000 × 4,000	
318.5	× 4.5 6.5 10.3	× 4,000 × 4,000 × 4,000	
* 355.6	× 4.0	× 4,000	

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-316L TP-A

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
355.6	× 5.0	× 4,000	
		× 6,000	
* 406.4	× 4.0	× 4,000	
		× 4,000	
		× 6,000	
		× 4,000	
* 457.2	× 4.0	× 6,000	
* 508	× 5.0	× 4,000	
		× 6,000	

SUS-310S TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
216.3	× 6.5	× 6,000	
267.4	× 6.5	× 6,000	
318.5	× 6.5	× 6,000	

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS329J4L (NAS64) TP-A

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
21.7	× 3.0	× 4,000	
27.2	× 3.0	× 4,000	
34.0	× 3.0	× 4,000	
42.7	× 3.0	× 4,000	
48.6	× 3.0	× 4,000	
	4.0	× 4,000	
60.5	× 3.0	× 4,000	
	4.0	× 4,000	
	5.5	× 4,000	
76.3	× 3.0	× 4,000	
	4.0	× 4,000	
89.1	× 3.0	× 4,000	
	4.0	× 4,000	
114.3	× 3.0	× 4,000	
	4.0	× 4,000	
	6.0	× 4,000	
139.8	× 3.0	× 4,000	
	4.0	× 4,000	
	5.0	× 4,000	
165.2	× 3.0	× 4,000	
	4.0	× 4,000	
	5.0	× 4,000	
	7.1	× 4,000	
216.3	× 3.0	× 4,000	
	4.0	× 4,000	
	6.5	× 4,000	
	8.2	× 4,000	
267.4	× 4.0	× 4,000	
	6.5	× 4,000	
	9.3	× 4,000	
318.5	× 5.0	× 4,000	
	6.5	× 4,000	
	10.3	× 4,000	
355.6	× 5.0	× 4,000	

SUS836L (NAS254N) TP-A 単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
21.7	× 3.0	× 4,000	
27.2	× 3.0	× 4,000	
34.0	× 3.0	× 4,000	
	4.0	× 4,000	
42.7	× 3.0	× 6,000	
48.6	× 3.0	× 4,000	
	4.0	× 4,000	
60.5	× 2.0	× 4,000	
	3.0	× 4,000	
76.3	× 3.0	× 4,000	
89.1	× 3.0	× 4,000	
	4.0	× 4,000	
114.3	× 2.0	× 4,000	
	3.0	× 4,000	
	4.0	× 4,000	
139.8	× 3.0	× 4,000	
	4.0	× 4,000	
165.2	× 3.0	× 4,000	
	4.0	× 4,000	
216.3	× 4.0	× 4,000	
267.4	× 4.0	× 4,000	

注) *印 355.6mm以上はTPY-S