

溶 接 管

SUS-316L TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕上 (F)
13.8	X 2.0	X 4,000	
17.3	X 2.0	X 4,000	
	3.0	X 4,000	
21.7	X 2.0	X 4,000	
	2.5	X 4,000	
	3.0	X 4,000	
27.2	X 2.0	X 4,000	
	2.5	X 4,000	
	3.0	X 4,000	
34	X 2.0	X 4,000	
	3.0	X 4,000	
		X 6,000	
	3.5	X 4,000	
42.7	X 2.0	X 4,000	
	3.0	X 4,000	
		X 6,000	
	3.5	X 4,000	
48.6	X 2.0	X 4,000	
	3.0	X 4,000	
		X 6,000	
	3.5	X 4,000	
60.5	X 2.0	X 4,000	
	3.0	X 4,000	
		X 6,000	
	3.5	X 4,000	
	4.0	X 4,000	
		X 6,000	
76.3	X 2.0	X 4,000	
	3.0	X 4,000	
		X 6,000	
	3.5	X 4,000	
	4.0	X 4,000	
	5.2	X 4,000	
	7.0	X 4,000	

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕上 (F)
89.1	X 2.0	X 4,000	
	3.0	X 4,000	
		X 6,000	
	4.0	X 4,000	
	5.5	X 4,000	
114.3	X 3.0	X 4,000	
	4.0	X 4,000	
	6.0	X 4,000	
139.8	X 3.0	X 4,000	
	3.5	X 4,000	
	4.0	X 4,000	
	5.0	X 4,000	
	6.6	X 4,000	
	9.5	X 4,000	
165.2	X 3.0	X 4,000	
	3.5	X 4,000	
	4.0	X 4,000	
	5.0	X 4,000	
	7.1	X 4,000	
216.3	X 3.0	X 4,000	
	4.0	X 4,000	
	6.5	X 4,000	
	8.2	X 4,000	
	12.7	X 4,000	
267.4	X 3.0	X 4,000	
	4.0	X 4,000	
	6.5	X 4,000	
	9.3	X 4,000	
318.5	X 3.0	X 4,000	
	4.0	X 4,000	
	4.5	X 4,000	
	6.5	X 4,000	
355.6	X 4.0	X 4,000	
		X 6,000	
406.4	X 4.0	X 4,000	
	5.0	X 4,000	
	8.0	X 6,000	

注) *印 355.6mm以上はTPY-S

溶 接 管

SUS-316L TP-A

単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕上 (F)
* 406.4	X 5.0	X 6,000	
	8.0	X 6,000	
	12.7	X 6,000	
* 457.2	X 5.0	X 6,000	
* 508	X 5.0	X 6,000	
	9.5	X 6,000	
* 558.8	X 6.0	X 6,000	
* 609.6	X 6.0	X 6,000	

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕上 (F)

注) *印 355.6mm以上はTPY-S