

(BA) 直管

SUS-304 TP-S-BA

単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
3	× 0.5	× 2,000	
	1.0	× 2,000	
3.18	× 0.5	× 2,000	
	0.72	× 2,000	
	1.0	× 2,000	
4	× 0.5	× 2,000	
	1.0	× 2,000	
5	× 0.5	× 2,000	
	0.8	× 2,000	
	1.0	× 2,000	
6	× 0.5	× 2,000	
		× 4,000	
	0.8	× 4,000	
6.35	× 0.5	× 2,000	
		× 4,000	
	0.89	× 2,000	
7	× 0.5	× 2,000	
		× 4,000	
	1.0	× 2,000	
8	× 0.5	× 2,000	
		× 4,000	
	0.8	× 4,000	
9	× 0.5	× 2,000	
		× 4,000	
	1.0	× 2,000	
9.53	× 0.89	× 4,000	
	1.0	× 2,000	
	1.24	× 4,000	
10	× 0.5	× 2,000	
		× 4,000	
	0.8	× 4,000	
	1.0	× 2,000	

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
10	× 1.0	× 4,000	
	1.5	× 4,000	
11	× 0.5	× 2,000	
		× 4,000	
	1.0	× 2,000	
12	× 0.5	× 2,000	
		× 4,000	
	1.0	× 2,000	
12.7	× 1.0	× 2,000	
		× 4,000	
	1.24	× 2,000	
13.8	× 1.2	× 4,000	
		× 4,000	
	1.0	× 4,000	
14	× 1.0	× 4,000	
		× 4,000	
15	× 1.0	× 4,000	
		× 4,000	
15.88	× 1.0	× 4,000	
	× 1.24	× 4,000	
17	× 1.0	× 4,000	
		× 4,000	
17.3	× 1.2	× 4,000	
		× 4,000	
18	× 1.0	× 4,000	
		× 4,000	
19	× 1.5	× 4,000	
		× 4,000	
19.05	× 1.24	× 4,000	
	1.65	× 4,000	
20	× 1.0	× 4,000	
		× 4,000	
21.7	× 1.65	× 4,000	
		× 4,000	
27.2	× 1.65	× 4,000	
		× 4,000	
34	× 1.65	× 4,000	
		× 4,000	

(BA) 直管

SUS-316 TP-S-BA

単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
1.58	× 0.4	× 2,000	
2	× 0.5	× 2,000	
3	× 0.5	× 2,000	
	1.0	× 2,000	
3.18	× 0.5	× 2,000	
	0.72	× 2,000	
		× 4,000	
	1.0	× 2,000	
4	× 0.5	× 2,000	
	1.0	× 2,000	
4.76	× 0.8	× 2,000	
5	× 1.0	× 2,000	
6	× 1.0	× 2,000	
		× 4,000	
	1.2	× 4,000	
	1.5	× 4,000	
6.35	× 0.89	× 2,000	
		× 4,000	
	1.0	× 2,000	
		× 4,000	
	1.24	× 4,000	
	1.65	× 4,000	
8	× 1.0	× 2,000	
		× 4,000	
	1.5	× 4,000	
9.53	× 0.89	× 2,000	
		× 4,000	
	1.0	× 2,000	
		× 4,000	
	1.24	× 4,000	
	1.65	× 4,000	
10	× 1.0	× 2,000	
		× 4,000	
	1.5	× 4,000	
12	× 1.0	× 4,000	
	1.2	× 4,000	
	1.5	× 4,000	
12.7	× 1.0	× 2,000	
		× 4,000	

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
12.7	× 1.24	× 2,000	
		× 4,000	
	1.65	× 4,000	
	2.11	× 4,000	
15.88	× 1.0	× 4,000	
	1.24	× 4,000	
	1.65	× 4,000	
19.05	× 1.24	× 4,000	
	1.65	× 4,000	

SUS-316L TP-S-BA

3.18	× 0.72	× 2,000	
6	× 1.0	× 4,000	
6.35	× 0.89	× 2,000	
		× 4,000	
	1.0	× 2,000	
		× 4,000	
8	× 1.0	× 4,000	
9.53	× 1.0	× 2,000	
		× 4,000	
	1.24	× 4,000	
10	× 1.0	× 4,000	
12	× 1.0	× 4,000	
12.7	× 1.0	× 2,000	
		× 4,000	
	1.24	× 2,000	
		× 4,000	
15.88	× 1.0	× 4,000	
19.05	× 1.24	× 4,000	
	1.65	× 4,000	
21.7	× 1.65	× 4,000	
25.4	× 1.65	× 4,000	
27.2	× 1.65	× 4,000	
34	× 1.65	× 4,000	
48.6	× 1.65	× 4,000	
60.5	× 1.65	× 4,000	

BA - コイル品

SUS-304 TP-S-BA

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
3	× 0.5	× 30M	
		× 50M	
	1.0	× 30M	
		× 50M	
3.18	× 0.5	× 30M	
		× 50M	
	0.72	× 30M	
4	× 0.5	× 30M	
		× 50M	
6	× 1.0	× 30M	
		× 50M	
		× 100M	
6.35	× 1.0	× 30M	
		× 50M	
8	× 1.0	× 30M	
		× 50M	
9.53	× 1.0	× 30M	
		× 50M	
10	× 1.0	× 30M	
		× 50M	
12	× 1.0	× 30M	
		× 50M	
12.7	× 1.0	× 30M	
		× 50M	

SUS-316 TP-S-BA 単位：mm

外 径 (O.D)	× 厚 さ (W.T)	× 長 さ (L)	仕 上 (F)
3	× 0.5	× 30M	
3.18	× 0.5	× 30M	
		0.72	
6	× 1.0	× 30M	
		× 50M	
		× 100M	
6.35	× 1.0	× 30M	
		× 50M	
8	× 1.0	× 30M	
		× 50M	
9.53	× 1.0	× 35M	
		× 57M	
10	× 1.0	× 30M	
		× 50M	
12	× 1.0	× 30M	

SUS-316L TP-S-BA

6	× 1.0	× 30M	
		× 50M	
		× 100M	
6.35	× 1.0	× 30M	
8	× 1.0	× 30M	
		× 50M	
9.53	× 1.0	× 30M	
10	× 1.0	× 30M	
		× 50M	

EP・WEP直管

SUS-316L TP-S-EP

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
3.18	× 0.72	× 2,000	
6.35	× 1.0	× 2,000 × 4,000	
9.53	× 1.0	× 2,000 × 4,000	
12.7	× 1.0 1.24	× 4,000 × 2,000 × 4,000	
19.05	× 1.24	× 4,000	
25.4	× 1.65	× 4,000	

SUS-316L TP-S-WEP 単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
3.18	× 0.72	× 2,000	
6.35	× 1.0	× 2,000 × 4,000	
9.53	× 1.0	× 2,000 × 4,000	
12.7	× 1.24	× 4,000	